




ENGINEERED FOR MOTION

216 Series Infrared "Touchless" Automatic Door Activation Switches



#216



#216-L



#216-N



1½" Self-Sticking Mylar
Face Plate Decal
(Blue Background/
White Legend)

Product Name

216 Series

Infrared "Touchless" Automatic Door
Activation Switches

Contact Information

MS SEDCO
7898 Zionsville Road
Indianapolis, IN 46268
Phone: (317) 842-2545
www.mssedco.com

Product Description

BASIC USE

The 216 Series touchless switches utilize active infrared technology to provide automatic door activation in a completely hands-free and germ-free manner. Ideal for use in ADA applications, health care facilities, clean rooms, bathrooms or any location where germ-free door activation is preferred. The 216 Series face plates are made of stainless steel and are available in 3 different sizes.

Technical Data

- ADA Compliant Hands-Free Operation
- Automatic Self-Changing ID Coding Eliminates Possible Electrical Interference
- Adjustable Reaction Time (0.05-1 Sec.)
- 12 to 24V AC or DC Operation
- Form C Relay Output
- Heavy Duty 3 Amp Contact
- Selectable Failsafe

SPECIFICATIONS

Detection Method

Amplitude modulated, coded carrier active infrared

Frequency Codes

Automatic self-changing

Avg. Radiated Power

Less than 18mW

Input Voltage

12V to 24V AC or DC, not polarity sensitive

Input Current

Approx. 100mA @ 18V AC

Relay Contacts

Form C rated at 3 amps @ 24V DC (resistive)

Relay Operation Modes

Normal or "fail-safe" (jumper selectable)

Response Time

Less than 0.3 seconds

Reaction Time

Adjustable from 0.05 to 1 sec.

Operating Distance

6 in. to 2.5 ft.

Unit Size (without face plate)

1 5/16"W x 4"H x 1 1/4"D

Mounting Options

Single-gang, 2-gang or door jamb mount

Face Plate Sizes

216 Fits Single-gang or 2-gang Box

4 1/2"W x 4 1/2"H

216-L Fits Single-gang Box

2 3/4"W x 4 1/2"H

216-N Fits Door Jamb

1 11/16"W x 4 1/2"H

Face Plate Finish

Brushed Stainless Steel

Temperature

-13 °F to 140 °F (-25 °C to 60 °C)

APPLICABLE STANDARDS

American National Standards Institute (ANSI) - Building Hardware Manufacturers Association (BHMA) - ANSI/BHMA A156.10 & A156.19.

Warranty

A one year warranty is available from the manufacturer covering defects in materials and workmanship. Contact MS SEDCO for details.

Installation & Maintenance

MS SEDCO recommends that all maintenance and adjustments be performed by an AAADM Certified Technician.

042020

216 Series
Infrared "Touchless"
Automatic Door Activation Switches



ENGINEERED FOR MOTION

DIMENSIONS

